



- Notes:
1. All Dimensions are in Millimeters.
  2. Operation voltage: 100 VAC max.
  3. Current rating : 1 Amps max.
  4. Contact resistance: 100m ohms max.
  5. Insulation resistance: 1000M ohms min. 500 VDC
  6. Dielectric withstanding voltage: 500 VAC / 1minute
  7. Operating Temperature: -20°C to +60°C
  8. Storage Temperature: -40°C to +70°C

RECOMMENDED P.C.B LAYOUT (TOP VIEW)

GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE	DESIGN UNITS
4 PLACES	± 0.10	N/A	METRIC
3 PLACES	± 0.25		
2 PLACES	± 0.38		
1 PLACE	± 0.50		
ANGULAR ± 5°			

  

CHECKED BY	DATE	THIRD ANGLE PROJECTION	TITLE
			WISE POWER TECH.CO.LTD

  

APPROVED BY	DATE	PART NO.	DOCUMENT NO.	SHEET NO.
	03/17/06	BS258-0001-10	BS258-0001-10	1 OF 1

  

SYMBOLS MAJOR CRITICAL		REVISION ON CAD ONLY
QUALITY	☒ = 0	
	▨ = 0	

10 9 8 7 6 5 4 3 2 1

A B C D E F