



RECOMMENDED P.C.B LAYOUT (TOP VIEW)

Notes:

- 1.All Dimensions are in Millimeters.
- 2.Current rating : 0.5 Amps max.
- 3.Contact resistance: 40m ohms max.
- 4.Insulation resistance: 1000M ohms min.DC500 V
- 5.Dielectric withstanding voltage: AC500V / 1minute
- 6.Operating Temperature: -20°C to +60°C
- 7.Storage Temperature: -40°C to +70°C

Ordering Info.: **B S 2 9 5 - 0 0 0 4 - 0 2**
 SERIES NO.

- PACKING TYPE
2..... tube
- INSULATOR COLOR
0..... black
- GOLD PLATING IN CONTACT AREA
4..... 0.25um (10u") Au

EC NO: New Release A DRWN: CH'KD: APPR:	REV DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)		SCALE N/A	DESIGN UNITS METRIC	WISE POWER TECH.CO.LTD			
			mm	INCH	THIRD ANGLE PROJECTION	TITLE			
		4 PLACES	± ---	± ---	DRAWN BY	DATE	1.8 inch HDD connector (H=2.63,standard type)50PIN		
		3 PLACES	± 0.12	± ---	CHECKED BY	DATE	SYMBOLS MAJOR CRITICAL QUALITY <input checked="" type="checkbox"/> =0 <input type="checkbox"/> =0	REVISE ON CAD ONLY	
2 PLACES	± 0.25	± ---	APPROVED BY	DATE	PART NO.	DOCUMENT NO.	SHEET NO.		
1 PLACE	± 0.40	± ---		03/21/07'	BS295-0004-02	BS295-0004-02	1 OF 1		
ANGULAR ± 3 °									